

RKP36U88DCPRO

Rack PRO



The 19" 800x1000 42U SERVER rack cabinet, due to its stability and load capacity, is designed for server rooms and the installation of multiple telecommunications, IT and audio/video equipment.

Its dimensions allow the adoption of vertical channels, for easy management of patch cords and optical patch cords, both front and back working, and the installation of racks up to 800 mm deep.

The fully demountable and easy to re-assemble structure makes it ideal in the presence of architectural barriers. The cabinet is delivered assembled.



Technical Chars

- Steel frame
- 4 adjustable uprights
- Grilled front door
- Removable side and rear panels
- Pre-arrangement on roof for installation of ventilation system
- Provision for cable access from below and above
- Adjustable feet

RKP36U88DCPRO		
Code		287884
Specifications		
Unit		36
Product dimensions	mm	800x800x1719
Net Weight	kg	91
Load capacity	kg	1000
Base and roof structure		
Material		Sheet steel
Thickness	mm	15/10
Predisposition		Pre-cut base for cable entry and roof for cooling fan installation.
External uprights		
Material		Sheet steel
Quantity		4
Thickness	mm	16/10

Side panels		
Typology		Removable with quick release 1/4 turn key
Quantity		2
Thickness	mm	10/10
Rear panel		
Typology		Removable with quick release 1/4 turn key
Thickness	mm	10/10
Front door		
Typology		Grill
Handle		Ergonomic retractable with key
Opening angle	°	110
Internal uprights		
Typology		Depth adjustable
Quantity		4
Material		Galvanised steel
Thickness	mm	16/10
Floor supports		
Typology		Adjustable feet
Quantity		4
Varnishing- rack		
Typology		Epoxy-polyester
RAL		9005
Colour		Black
Packaging		
Pieces		1
Packaging dimensions	mm	800x800x1719

Rack cabinet details

