

**PAS4036104**

## Coaxial cables



Indoor 6,6 mm cable, Cu inner conductor material and Eca CPR compliance; white PVC jacket material.

initial_fields		
Code		PAS4036104
Capacity		52
Propagation speed	%	85%
Minimum bending radius	mm	35
Resistance	Ohm/Km	22.5
Inner conductor resistance	Ohm/Km	27
Dielectric		
Material		PEE
Diameter		4.7
Antimigrating foil		
Antimigrating foil		PET
Screen		
Foil material		Al/PET
Foil coverage		100%
Braid material		Al
Braid Coverage		35%
Inner conductor		
Material		Cu
Diameter	mm	1.0
External sheath		
Material		White PVC
Diameter	mm	6.7

Return loss		
30-470 MHz	dB	>30
470-862 MHz	dB	>25
862-1750 MHz	dB	>20
1750-2400MHz	dB	>20
Attenuation (100m)		
Attenuation 5	dB	1.6
Attenuation 50	dB	4.6
Attenuation 200	dB	9.0
Attenuation 470	dB	14.5
Attenuation 800	dB	18.6
Attenuation 1000	dB	19.8
Attenuation 1350	dB	23.3
Attenuation 1750	dB	27.0
Attenuation 2150	dB	31.7
Attenuation 2400	dB	33.2
Attenuation 2700	dB	35.8
Screening efficiency		
5-30 MHz	dB	>65
30-1000MHz	dB	>75
1000-2150MHz	dB	>80
Shielding class (EN-50117-9-2)		B
Dimensions and packaging		
Pieces		400
EAN code		8016978052493
Multiple EAN		8016978052493
Packaging dimensions	mm	550 x 280 x 290
Packaging weight	Kg	17.2